

Simultaneously display and log 4 channels

Same as 4 Channel Thermometer but able to automatically record and store up to 16,000 data points in the field, which can later be downloaded to your computer. This model also comes with the RS232 computer cable 800001, and software 840004, and does not have a relative function. N.I.S.T. Traceable Certificate of Compliance available.

DIM: 7¼" × 2½" × 1¼" (184 × 64 × 32 mm). WEIGHT: 8.4 oz (238 g).



No.	Description	Each
800024	4 Channel Datalogging Therm.	\$304.00
800024C	4 Channel Data. Therm. Certified	\$338.00
800001	RS232 71" Cable (Included)	\$36.00
800003	AC Adaptor	\$17.00
800060-77	Type K Thermocouple Probes	\$18.00+
840004	Software (Included)	\$43.00
840094	RS232 to USB Adaptor Cable	\$24.00
840089	Rubber Holster	\$12.00
840090	Water Resistant Instrument Pouch	\$11.00
840093	Field Tripod	\$32.00

Range	Accuracy	Resolution
-200 ~ 200°C	±0.2% reading +1°C	-200 ~ 200°F, 0.1°F, else 1°F (-200 ~ 200°C, 0.1°C; 200 ~ 1370°C 1°C)
200 ~ 400°C	±0.5% reading +1°C	
400 ~ 1370°C	±0.2% reading +1°C	
-328 ~ 200°F	±0.5% reading +2°F	
-200 ~ 200°F	±0.2% reading +2°F	
200 ~ 2498°F	±0.3% reading +2°F	



A2B-Lab

Rue Ibnou Katir - Résidence El Beida, Imm. B, Apt. 22 20380 Casablanca - Maroc Tél: +212 (0)5 22 98 66 19 Fax: +212 (0)5 22

Email: contact@a2b-lab.ma

Web: www.a2b-lab.ma